

Dispenser



Dispenser 750
on standard L-frame

Standard

L-frame	Pump combination 2 c
Adjustable dosing ratio	Separate outlets resin and catalyst
No flushing	

Options

Cart with boom	Mixing station with static mixer
Catalyst failure control	3 rd or 4 th component
Housing	Siemens plc
Extension casting head or mat impregnation	

Product Information

The clean and exactly way of metering and mixing...

Wolfangel dispenser and metering systems allow an economical use of your raw materials. You take the quantity you need and always in the right dosing ratio.

With the optional mixing head with hose and casting head you pour the material directly to your mould. Clean and easy without filling any buckets.

Dispenser	150	300	750	1000	25 EP
Power			Druckluft		
Power supply	18,5:1	9,2:1	2,5:1	1,75:1	
Max. air pressure			6 bar		
Air consumption	600 l/min		900 l/min		170 l/min
Capacity per double stroke	150 ccm	300 ccm	750 ccm	1000 ccm	25 ccm
Max. output <small>(dep. on viscosity, hose length and diameter)</small>	~ 2,2 l/min	~ 4,5 l/min	~ 11,0 l/min	~ 15,0 l/min	~ 0,5 l/min
Dosing ratio	1,1 – 3,4 %	1,4 – 3,5 %	1,4 – 3,5 %	1,0 – 2,8 %	100:18 100:39

Subject to technical modifications



Dispenser 1000 M
or solid surface



Dispenser 25 M
Epoxy version with plc

